



www.coilwindingmachines.eu

Tel: +44(0)1684 273164 Fax: +44(0)1684 273171 Email: enquiry@ingridwest.co.uk by Ingrid West Machinery Ltd

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

Multi Axis Automatic Winding Machine 12 Spindle version.

Application:

Relays, Automotive ABS coils, LCD coils, transformers, ignition coils, inductors, sensor coils, solenoids DVD reader, Inverter, Switching Power Supplies, Ballast Transformer and other bobbin-wound products....

Main features:

- The wire guide movement can be freely programmed in all 3 axes (X, Y, and Z).
- Wraps either radial or axial pins, - programmable nozzle movement through 0°, and 90° angles.
- Wire cutting on bobbin pin, nozzle cut or nipper. Method can be chosen by operator and setup in the program.
- Password function, prevent accidental program change.
- Simplified programming with teach-in programming system using 15" touch screen.
- Easy to change tooling and machine set-up recalled from the onboard computer when changing product.
- Fully CE compliant.

Options:

- Automatic load / unload system.
- Load and unload shuttle transfer system (as shown below).
- Skeining (twisting) unit.
- Customised accessories to suit your application.



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

Main technical specifications

No. of spindles	12
Wire size	0.02-0.3 mm
Max traverse width	85 mm
Spindle pitch	55 mm
Max bobbin diameter	45 mm
Spindle speed	12,000 rpm
Spindle position accuracy	+ 0.1°
Guide head drive motor	200W AC servomotor X , Y and Z axis
Max movement of guide head	X(left/right) 100 mm Y(front/back) 75 mm Z(up/down) 65 mm
Nozzle positions	0°, 90° or 120°
Max pin wrap speed	150 Turns / min
Control system	Windows interface PC with USB connector & DVD ROM
Interface	RS232 or USB
Touch screen	15 inch
Air supply	6 Bar
Power supply	single phase 220V +-10% 50Hz
Power consumption	3kVA
Weight	650 Kg
Dimensions (cm)	110(W) x 150(L) x 155(H) – excluding wire spool stand



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.