



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

## WH 200 Hook winder.

### Specification

**Program** Digital controller capable of holding data for 999 winding operations, Fully programmable pitch per turn (wire spacing). Start position, winding direction and segment winding angle programmable.  
In semi-automatic mode, hold-time is programmable at top and bottom of stroke

**Control** Pneumatically operated hook  
Mechanically adjustable stroke length  
Turns counted digitally

**Full control of core rotation using stepping motor**

**Package** Includes full height cabinet, digital controller and one hook  
Air cylinder, filter & regulator;  
stepper motor system

**Hook sizes** 3 standard hook sizes, with specials available

**Wire size** 0.3 ~ 2.2 mm

**O.d. range** 15 ~ 80 mm

**Air supply** Typically 5 Bar

**Power supply** AC 230 /110 V ± 10%, 50 – 60 Hz

**Dimensions** 70 x 55 x 150 cm

### Hook data

Hook type	H5	H8	H10
Hook size	5 mm	8 mm	10 mm
Min. finished i.d.	8 mm	11 mm	14 mm



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

**~ Coil winding solutions you can rely on ~**



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.