



[www.coilwindingmachines.eu](http://www.coilwindingmachines.eu)

Tel: +44(0)1684 273164 Fax: +44(0)1684 273171 Email: [enquiry@ingridwest.co.uk](mailto:enquiry@ingridwest.co.uk) by Ingrid West Machinery Ltd

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

## WH 766T Skeining Six spindle coil winding machine.

### Specification

Programming	Microprocessor controlled, capable of holding 999 program sequences, which may be run independently or in selected blocks for compound windings.
Control	Spindle drive - High torque brushless DC induction motor producing a max torque of 78.5Ncm. Traverse - Constant current driven 4-phase stepper motor.
Application	Designed for thin wires that require skeining. Nozzle type wire feeder heads on each spindle; these have adjustable parallelism so that multiple winding may be carried out. Each spindle is fed via a separate tension unit through a skeining device. <b>Automated skein function</b> - The winding is stopped a few turns from the end, and the machine automatically performs the skeining function. Half of the skeined length is then wound into the bobbin, and the remaining skeined length is used for the start of the next coil.
Package	Includes 6 x nozzle type wire feeder heads, 6 x skeiner units, and comprehensive manual.
Wire size	0.03 – 0.30mm
Max pitch	10 mm
Winding width	100 mm (max)
Bobbin dia.	100 mm (max)
Turns	9999.9 turn or 99999
Max speed	6000 rpm
Power	AC 230 / 110 V $\pm$ 10%, 50 – 60 Hz
Net weight	85 kg
CE cert. no.	AE9955093 01



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

**~ Coil winding solutions you can rely on ~**



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

## Tensioners - Fine wire, low cost.

### Specification

These mechanical tensioners provide precision control of winding tension for wires in the range from 0.02mm to 2.0 mm.

The arm position provides feedback to the system, adjusting the main friction wheel to regulate and maintain constant tension during the winding cycle.

Felt pads provide pre-tension and remove dust and other debris from the wire.

Ceramic eyelets and roller guides at each point of contact protect insulation from mechanical damage, and guide the wire.

The performance of these units is exceptional given the low cost, providing outstanding value for money.

\* The wire sizes shown are a guide only, for copper magnet wire at recommended "Standard Tension". The tension required in practical applications may vary considerably.



Models TC3S ~ TCM	Model TCL-X / TCLL-X
----------------------	----------------------

Model Type	Min Tension (grams)	Max Tension (grams)	Min Wire Gauge (mm) *	Max Wire Gauge (mm) *
TC3S	2	11	0.02	0.04
TCSS-X	7	30	0.03	0.06
TCSS	9	50	0.04	0.08
TCS-E	20	130	0.06	0.13
TCS	40	200	0.08	0.16
TCM	90	500	0.16	0.25
TCL-X	200	2000	0.20	0.60
TCLL-X	1000	5000	0.50	1.2

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

## ~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.