



www.coilwindingmachines.eu

Tel: +44(0)1684 273164 Fax: +44(0)1684 273171 Email: enquiry@ingridwest.co.uk by Ingrid West Machinery Ltd

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

Multi Axis Automatic Winding Machine

8 Spindle version.

Application:

Relays, Automotive ABS coils, LCD coils, transformers, ignition coils, inductors, sensor coils, solenoids DVD reader, Inverter, Switching Power Supplies, Ballast Transformer and other bobbin-wound products....

Main features:

- The wire guide movement can be freely programmed in all 3 axes (X, Y, and Z).
- Wraps either radial or axial pins, - programmable nozzle movement through 0°, and 90° angles.
- Wire cutting on bobbin pin, nozzle cut or air nipper. Method can be chosen by operator and setup in the program.
- Password function, prevent accidental program change.
- Simplified programming with teach-in programming system using 15" touch screen.
- Easy to change tooling and machine set-up recalled from the onboard computer when changing product.
- Fully CE compliant.

Options:

- Air nipper for larger wire.
- Load and unload transfer system (as shown).
- Skeining (twisting) unit (as shown).
- Customised accessories to suit your application.



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

Main technical specifications	
No. of spindles	8
Wire size	0.02-0.5 mm
Max traverse width	85 mm
Spindle pitch	55 mm
Max bobbin diameter	50 mm – 25 mm if load unload system used
Spindle speed	18,000 rpm
Spindle position accuracy	=> 0.1°
Guide head drive motor	200W AC servomotor X , Y and Z axis
Max movement of guide head	X(left/right) 100 mm Y(front/back) 75 mm Z(up/down) 65 mm
Nozzle positions	0°, 90° or 120°
Max pin wrap speed	150 Turns / min
Control system	Windows interface PC with USB connector & DVD ROM
Interface	RS232 or USB
Touch screen	15 inch
Air supply	6 Bar
Power supply	single phase 220V +-10% 50Hz
Power consumption	3 KVA
Weight	540 Kg
Dimensions (cm)	110(W) x 130(L) x 155(H) – excluding wire spool stand



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.