



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

E-1200 C WINDING MACHINE

DESCRIPTION.

Robust and reliable, the E-1200C winding machine is a floor standing style winding machine.

The sturdy chassis is manufactured from heavy gauge welded steel for durability, painted for ease of cleaning and maintenance.

The machine consists of a headstock with speed change, face plate, and pedal.

Due to the intended application of this machine, it does not have a bench or wire guiding system

This machine is specially designed for the manufacture of solenoids and power and distribution transformers from 10 to 1.200 KVA, using aluminium or copper wires, including rectangular or flat wires.



TECHNICAL CHARACTERISTICS.

- Maximum winding shaft speed. 500 r.p.m
- Winding shaft slow speed. 0 – 20-60-120 r.p.m
- Maximum coil diameter. 1,600 mm
- Maximum torque (low speed) 80 Kgm
- Main motor. 5 HP (3.7 kW)
- Power source. 3 x 380Vca - 50Hz
- Air supply 6 bar (minimum)

Delivery 90 DAYS from confirmation of the order.

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.