

EZ-H5 TENSIONER

For Heavy Duty Winding Machines

DESCRIPTION

The EZ-H5 is a floor standing style heavy duty tensioner. Suitable for wires 0.5 to 5mm in diameter.

For maximum stability, provision has been made to enable this unit to be bolted to the floor.

The wire is perfectly guided as soon as it leaves the supply spool, through clips with soft felt pads and a set of adjustable pulleys to give the desired pre-tension, according to the thickness of the wire and without damaging the insulation.

The brake pulley is controlled by two brakes, with independent pneumatic regulation for each. One of the brakes regulates the tension that is to be applied to the wire while winding and the other brake has a servo-control to maintain this tension as constant as possible, depending on the form of the coil being wound.



The pneumatic regulation is made by means of two pressure regulators (one for each pneumatic cylinder) which are incorporated in a box with air pressure gauges. This box may be situated in the most comfortable position and as close to the operator as necessary, thus avoiding unnecessary trips back and forth and production loss.

There is adjustable height positioning of the de-reeling cone on the column to match your supply spool height.



Maximum spool diameter ..500 mm

Maximum spool height650 mm


Working method..... Pneumatic

Dimensions (mm)670x540x1755

Weight95 Kg

DELIVERY TIME60 Days from order confirmation.

(Please confirm at time of order)



We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

COIL WINDING SOLUTIONS YOU CAN RELY ON

WORKING WITH LOCAL PARTNERS IN THE FOLLOWING COUNTRIES; Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

