



WH 800i Mașina de bobinat transformatoare, cu două axe.

Specificatii

Program	Controlată de microprocesor, capabilă să memoreze 999 secvențe programabile, care pot rula independent sau selectate în blocuri pentru bobinaje compuse.
Actionare	Axelor (arborilor) - Motor ce CC fara peri cu cuplu maxim de 78,5 Ncm. Avans lateral (pas) – motor pas cu pas cu comanda in curent.
Aplicatie	Ghidaje de fir tip duza alimenteaza fiecare axa, acestea sunt reglabile astfel incit bobinari duble pot fi realizate perfect. Fiecare ghidaj este alimentat printr-o unitate de tensionare separata.
Continut colet	2 x ghidaje de fir tip duza, 2 x unitați de tensionare, plus un dispozitiv pentru banda de izolat
Diam. cond	0.02 – 0.8 mm
Pas maxim	10 mm
Latime bobinei	200 mm (max)
Diam. bobinei	110 mm (max)
Viteza maxima	6000, 3000 or 1600 rpm
Alimentare	AC 230 / 110V ± 10%, 50-60Hz
Dimeniuni	760 x 680 x 720 mm
Greutate neta	37 kg
CE/TÜV	AE9955093 01



Ne dorim sa fim mai mult decit un furnizor de masini. Echipa noastra are a vasta experienta si est dispusa sa ofere support si consultanta in taote aspectele , de la proiectarea diespztivelor la alegerea masinilor si reglajul acestora.

Ingrid West Machinery

~ Coil winding solutions you can rely on ~

Romanian partner:

THONAUER AUTOMATIC SRL

Cím: Str Diligentei nr. 5, Bucuresti, 031555 Romania

Tel:+40 736 386 017 Fax: +40 21 336 95 34

Email: sergiu.czompi@thonauer.ro





Tensioners - Fine wire, low cost.

Specification

These mechanical tensioners provide precision control of winding tension for wires in the range from 0.02mm to 1.2 mm.

The arm position provides feedback to the system, adjusting the main friction wheel to regulate and maintain constant tension during the winding cycle.

Felt pads provide pre-tension and remove dust and other debris from the wire.

Ceramic eyelets and roller guides at each point of contact protect insulation from mechanical damage, and guide the wire.

The performance of these units is exceptional given the low cost, providing outstanding value for money.



Model TCL-X/TCLL-X

Models TC3S - TCM

* Copper magnet wire at recommended "Standard Tension"

Model Type	Min Tension (grams)	Max Tension (grams)	Min Wire Gauge (mm) *	Max Wire Gauge (mm) *
TC3S	2	11	0.02	0.04
TCSS-X	7	30	0.03	0.06
TCSS	9	50	0.04	0.08
TCS-E	20	130	0.06	0.13
TCS	40	200	0.08	0.16
TCM	90	500	0.16	0.25
TCL-X	200	2000	0.20	0.60
TCLL-X	1000	5000	0.50	1.2

Ne dorim sa fim mai mult decat un furnizor de masini. Echipa noastra are a vasta experienta si est dispusa sa ofere support si consultanta in taote aspectele , de la proiectarea diespzitivelor la alegerea masinilor si reglajul acestora.

Ingrid West Machinery

~ Coil winding solutions you can rely on ~

Romanian partner:

THONAUER AUTOMATIC SRL

Cím: Str Diligentei nr. 5, Bucuresti, 031555 Romania

Tel: +40 736 386 017 Fax: +40 21 336 95 34

Email: sergiu.czompi@thonauer.ro

