Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

## WH-S01 Wire Stripping Machine.

## **Specification**

Features A fast and inexpensive method of wire stripping. To strip the wire, simply insert the end

of the enamelled wire, turn by 90 degrees and then remove the stripped wire.

Wire Range 0.1 – 8.0 mm, - adjustable screw

Tooling Removal of enamel coating on copper wire using 0.1mm/0.2mm wire

brushes or solid fibreglass wheel

Application Wire enamel removal

Stripping Single wire only

Mounting Bench mounted, for

stable operation

Power supply 110 / 220 / 240 VAC

50 / 60 Hz

Dimensions (mm) 390 L \* 180 W \* 180 H

Weight 16kgs



I here are 3 brush types available, each suited to a specific wire range.		
P/N	Wire range	Description
S01-0.06mm	0.1mm - 0.2mm	Steel brushes with 0.06mm wire
		Set of two
S01-0.1mm	0.2mm - 0.3mm	Steel brushes with 0.1mm wire
		Set of two
S01-0.2mm	> 0.3mm	Steel brushes with 0.2mm wire
		Set of two

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

~ Coil winding solutions you can rely on ~



