



Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

## WH-TP01 Core taping machine.

### Specification

**Features:** Automatic taping with bobbin change-over. Tape cutter with start and finish wiper and automatic unload. 2 handed start button operation. Number of turns of tape is programmable from 1 to 9 turns.

**Cycle time:** Typically 3 seconds per bobbin for 2 turns of tape, cut and auto unload.



**Application:** Taping of ferrite cores, EI laminations and wound coils.

**Min. Bobbin Size:** 12mm of wound coil cross section.

**Supply reel dia:** 76mm I.D. standard - other sizes available.

**Changeable Parts:** Tape roller attachment, winding jigs (tooling), cutter and wiper fixture, safety cover, tape backing removal feature.

**Tape width (Max):** 50mm.

**Power supply:** 110 / 220 / 240 VAC 50 / 60 Hz.

**Dimensions:** 600 L \* 350 W \* 300 H

Bobbin range / sizes	<b>WH-TP01</b>
Ferrite core taping (Max)	EI-48
Ferrite core taping (Min)	EI-16
Insulation taping (Max)	EI-61
Net weight	45Kgs

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

## ~ Coil winding solutions you can rely on ~



Working with local partners in the following countries;

Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.