

## WH 800I MAȘINA DE BOBINAT TRANSFORMATOARE, CU DOUĂ AXE.

### SPECIFICATII

<b>Program</b>	Controlată de microprocesor, capabilă să memoreze 999 secvențe programabile, care pot rula independent sau selectate în blocuri pentru bobinaje compuse.
<b>Actionare</b>	Axelor (arborilor) - Motor ce CC fara peri cu cuplu maxim de 78,5 Ncm. Avans lateral (pas) - motor pas cu pas cu comanda in curent.
<b>Aplicatie</b>	Ghidaje de fir tip duza alimenteaza fiecare axa, acestea sunt reglabile astfel incit bobinari duble pot fi realizate perfect. Fiecare ghidaj este alimentat printr-o unitate de tensionare separata.
<b>Continut colet</b>	2 x ghidaje de fir tip duza, 2 x unitați de tensionare, plus un dispozitiv pentru banda de izolat.
<b>Diam. cond</b>	0.02 - 0.6 mm
<b>Pas maxim</b>	10 mm
<b>Latime bobinei</b>	110 mm (max)
<b>Diam. bobinei</b>	110 mm (max)
<b>Viteza maxima</b>	6000, 3000 rpm
<b>Alimentare</b>	AC 230 / 110V ± 10%, 50-60hz
<b>Dimeniuni</b>	760 x 680 x 720 mm
<b>Greutate neta</b>	37 kg
<b>CE/TÜV</b>	AE9955093 01



Ne dorim sa fim mai mult decit un furnizor de masini. Echipa noastra are a vasta experienta si est dispusa sa ofere support si consultanta in taote aspectele , de la proiectarea diespztivelor la alegerea masinilor si reglajul acestora.

**COIL WINDING SOLUTIONS YOU CAN RELY ON**

**komax**

Romanian partner: Mr Sergiu Czompi

Str. Preciziei nr. 1C | Romania | +40 21 335 5654 | info.buc@komaxgroup.com



## TENSIONERS - FINE WIRE, LOW COST

### SPECIFICATION

These mechanical tensioners provide precision control of winding tension for wires in the range from 0.02mm to 2.0 mm.

The arm position provides feedback to the system, adjusting the main friction wheel to regulate and maintain constant tension during the winding cycle.

Felt pads provide pre-tension and remove dust and other debris from the wire.

Ceramic eyelets and roller guides at each point of contact protect insulation from mechanical damage, and guide the wire.

The performance of these units is exceptional given the low cost, providing outstanding value for money.



Models TC3S ~ TCM

Model TCL-X / TCLL-X

\* The wire sizes shown are a guide only, for copper magnet wire at recommended "Standard Tension".

The tension required in practical applications may vary considerably.

Model Type	Min Tension (grams)	Max Tension (grams)	Min Wire Gauge (mm) *	Max Wire Gauge (mm) *
TC3S	2	11	0.02	0.04
TCSS-X	7	30	0.03	0.06
TCSS	9	50	0.04	0.08
TCS-E	20	130	0.06	0.13
TCS	40	200	0.08	0.16
TCM	90	500	0.16	0.25
TCL-X	200	2000	0.20	0.60

Ne dorim sa fim mai mult decat un furnizor de masini. Echipa noastra are a vasta experienta si est dispusa sa ofere support si consultanta in taote aspectele , de la proiectarea diespzitivelor la alegerea masinilor si reglajul acestora.

**COIL WINDING SOLUTIONS YOU CAN RELY ON**

**komax**

Romanian partner: Mr Sergiu Czompi

Str. Preciziei nr. 1C | Romania | +40 21 335 5654 | info.buc@komaxgroup.com

