

**Contact us**

Tel: +44 (0) 1684 273164

Email: enquiry@ingridwest.co.uk

## TWIN SPOOL TENSIONER/ACCUMULATOR



The tensioning device provides wire tension by applying a braking force to the wire spool, eliminating the possibility of causing damage to the wire insulation.

Horizontal de-spooling prevents twists in the wire, and the device is recommended for use with wires from 1.5 mm to 3 mm Ideal for Litz (multi stranded) wire.

The accumulator device allows tension to be controlled, removing up to 300 mm of “slack” or “Back” tension, caused by long flat sides of the bobbin, or if the operator needs to un-wind turns during the process.

Wire tension is adjusted by simple pneumatic controls. Both the tensioner and accumulator can be switched on and off remotely for maximum operator convenience.

I.e. released at the end of the winding to allow the operator to terminate the wire, and is then tension is re-applied for the next winding.

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

### COIL WINDING SOLUTIONS YOU CAN RELY ON

WORKING WITH LOCAL PARTNERS IN THE FOLLOWING COUNTRIES; Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

