

WH-TP01 CORE TAPING MACHINE

SPECIFICATION

- Features:** Automatic taping with bobbin change-over. Tape cutter with start and finish wiper and automatic unload. 2 handed start button operation. Number of turns of tape is programmable from 1 to 9 turns.
- Cycle time:** Typically 3 seconds per bobbin for 2 turns of tape, cut and auto unload.
- Application:** Taping of ferrite cores, EI laminations and wound coils.



- Min. Bobbin Size:** 12 mm of wound coil cross section.
- Supply reel dia.:** 76 mm I.D. standard - other sizes available.
- Changeable Parts:** Tape roller attachment, winding jigs (tooling), cutter and wiper fixture, safety cover, tape backing removal feature.
- Tape width (Max):** 50 mm
- Power supply:** 110 / 220 / 240 VAC 50 / 60 Hz.
- Dimensions:** 600 L * 350 W * 300 H
- Net weight:** 33 kg

Bobbin range / sizes	WH-TP01
Ferrite core taping (Max)	EI-48
Ferrite core taping (Min)	EI-16
Insulation taping (Max)	EI-61

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

COIL WINDING SOLUTIONS YOU CAN RELY ON

WORKING WITH LOCAL PARTNERS IN THE FOLLOWING COUNTRIES; Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.



REPRESENTING